

**【比較表】**

一般配管 (JIS規格sch10)			サニタリー配管 (IDF/ISO規格)		
呼び径	外径	板厚	呼び径	外径	板厚
6A	Φ10.5	1.2t	6A	Φ10.5	1.2t
8A	Φ13.8	1.65t	8A	Φ13.8	1.65t
10A	Φ17.3	1.65t	10A	Φ17.3	1.65t
15A	Φ21.7	2.1t	15A	Φ21.7	2.1t
			1.0S	Φ25.4	1.2t
20A	Φ27.2	2.1t			
			1.25S	Φ31.8	1.2t
25A	Φ34.0	2.8t			
			1.5S	Φ38.1	1.2t
32A	Φ42.7	2.8t			
40A	Φ48.6	2.8t			
			2.0S	Φ50.8	1.5t
50A	Φ60.5	2.8t			
			2.5S	Φ63.5	2.0t
65A	Φ76.3	3.0t	3.0S	Φ76.3	2.0t
80A	Φ89.1	3.0t	3.5S	Φ89.1	2.0t
90A	Φ101.6	3.0t	4.0S	Φ101.6	2.0t
100A	Φ114.3	3.0t	4.5S	Φ114.3	3.0t
125A	Φ139.8	3.4t	5.5S	Φ139.8	3.0t
150A	Φ165.2	3.4t	6.5S	Φ165.2	3.0t
200A	Φ216.3	4.0t	200A	Φ216.3	4.0t